

**AN/PRC-74
Radio Set**

NSN: 5820-00-912-3991 (AN/PRC-74)
5820-00-926-7282 (AN/PRC-74A)
5820-00-935-0030 (AN/PRC-74B)
5820-00-177-1641 (AN/PRC-74C)

Reference: TM 11-5820-590-12
TM 11-5820-590-12-1

General Information

The AN/PRC-74 is a low-power, transistorized, SSB radio set used for voice and CW communications. It is designed primarily as a manpack set in areas where direct line of sight (LOS) communications are not possible. Except for the difference in the frequency range of the AN/PRC-74B and AN/PRC-74C, all models are essentially the same. Current tactical speech security equipment is not compatible with the AN/PRC-74; therefore, secure voice is not a mode of operation. Coder-Burst Transmission Group AN/GRA-71 can be used with all lettered models.

Technical Characteristics

Frequency Range	2.0 to 11.999 MHz (AN/PRC-74 and AN/PRC-74A); 2.0 to 17.999 MHz (AN/PRC-74B and AN/PRC-74C)
Planning Range	40 km (25 mi) ground wave; refer to sky wave propagation chart to determine medium range, FM 11-486-6
Number of Channels	10,000 spaced every 1 kHz (AN/PRC-74 and AN/PRC-74A); 16,000 spaced every 1 kHz (AN/PRC-74B and AN/PRC-74C)
Power Input	10.5 to 17 V DC, 12 to 31 V DC or 110/220 V AC
Power Source	Battery (BA-30, 70 each or BB-418/U, 10 each); vehicle power system (requires PP-4514/PRC-74); any appropriate AC power source (requires use of PP-4514/PRC-74)
Power Output	15 W PEP
Antenna	AS-1887/PRC-74, slanted wire and dipole
Tuning	Detent
Type of service	-3 K00J3E, 100HA1A
Weight	18.8 kg (41.5 lb) with dry Battery BA-4386/U, two each; 13.4 kg (29.5 lb) with wet Battery BB-418/U, 10 each; 22.7 kg (50 lb) with PP-4514/PRC-74

AN/PRC-74 Radio Set

