


STATUS: Standard  
 CLASSIFICATION OF EQUIPMENT: Unclassified  
 USING SERVICE: Navy  
 DATE OF THIS SHEET: 8 May 52

# AN/FGA-TYPE

AN/COMP TYPE NUMBER: TT-45/FG, TT-46/FG  
 REPERFORATOR



TT-45/FG

Reperforators TT-45/FG and TT-46/FG are automatic, receiving only teletypewriter units which produce perforated tape, with typing, of messages received. It is used in tape-relay, and similar teletypewriter communication applications.

These equipments consist essentially of commercial (Teletype Corp. Model 14), receiving only, typing reperforators.

They include a table to support the reperforator unit.

TT-45/FG is identical with the TT-46/FG, except that the latter has a governed-series motor.

<b>AN/FGA-TYPE</b>		INSTRUCTION LITERATURE: NavShips 91241
		CLASSIFICATION OF EQUIPMENT: Unclassified
TT-45/FG, TT-46/FG	:AN/COMP TYPE NUMBER	USING SERVICE: Navy
REPERFORATOR		DATE OF THIS SHEET: 8 May 52

**MAJOR COMPONENTS**

QUANT	NAME OF COMPONENT	DIMENSIONS (IN) INSTALLED	WEIGHT (LBS)
1	Typing Reperforator FPRC23H246	11-1/2 x 15-3/4 x 13	Not Available
1	Rectifier REC29	Not Available	" "
1	Relay RY30	" "	" "
1	Base FB46/15	" "	" "
1	Table XRT200AA	26-1/8 x 18 x 21-5/16	" "
1	Electrical Assembly 105014	Not Available	" "

**OPERATIONAL CHARACTERISTICS**

**TACTICAL USE:** Teletype receiving and distributing stations.

**INSTALLATION:** Ground, fixed or transportable.

**CAN COMMUNICATE WITH:** Five unit code teletype transmitting equipment, geared for 368 opm.

**TECHNICAL CHARACTERISTICS**

**OPERATING FUNCTIONS:** Prints incoming messages and perforates the tape so that the messages can be relayed to other stations.

**OPERATING SPEED:** 368 opm.

**MOTOR CHARACTERISTICS:** Synchronous motor in TT-45/FG, series (governed) motor in TT-46/FG.

**POWER REQUIREMENTS:** 115 v, 60 cyc, 1 phase, ac.

**PHYSICAL CHARACTERISTICS**

Information on Reperforators TT-45/FG and TT-46/FG not available.