

Section I. Teletypewriter Equipment

AN/FGC-20, AN/FGC-20X, AN/FGC-64, AN/FGC-66, AN/UGC-4, AN/FGC-159, and AN/FGC-160 Teletypewriter Sets and TT-259/FG Teleprinter

Status: STD-B; NSN: 5815-00-503-2652 (AN/FGC-20)
 STD-B; NSN: 5815-00-392-7743 (AN/FGC-20X)
 STD-B; NSN: 5815-00-817-9277 (AN/FGC-66)
 STD-B; NSN: 5815-00-557-5970 (AN/UGC-4)
 STD-A; NSN: 5815-00-561-7964 (AN/FGC-159 and 159X)
 STD-A; NSN: 5815-00-025-9036 (AN/FGC-160)
 STD-A; NSN: 5815-00-688-8761 (TT-259/FG)

Reference: TM 11-5815-200-12

General Information

These teletypewriter sets provide a means of hard-copy record traffic. They may be operated in fixed and mobile environments. All sets except the TT-259/FG can supply line current. All sets are similar in appearance except the TT-259/FG; it has no keyboard. Major functional differences are covered in the technical manual.

Technical Characteristics

Method of Transmitting-----Keyboard
 Method of Receiving-----Page copy
 Type of Signal:
 AN/FGC-159 and AN/FGC-160-----60 microampere polar
 All others-----20 or 60 mA DC neutral, or 20 or 30 mA DC
 polar
 Operation Mode-----Half duplex or full duplex except
 TT-259/FG which is a receive page
 printer only
 Speed Option-----60, 66, 75, and 100 wpm
 Power Requirement:
 TT-259/FG-----95 to 125 V AC, 60 Hz
 AN/FGC-20, -159, -160-----95 to 125 V AC or 190 to 250 V AC, 60 Hz
 AN/FGC-20X, -64, -66, AN/UGC-4-----95 to 125 V AC or 190 to 250 V AC, 50
 to 60 Hz
 Weight-----57.6 kg (127 lb)

**AN/FGC-20, AN/FGC-20X, AN/FGC-64,
AN/FGC-66, AN/UGC-4, AN/FGC-159, and
AN/FGC-160 Teletypewriter Sets and
TT-259/FG Teleprinter**

