

## Beam Power Tube

### NOVAR TYPE

For Horizontal-Deflection-Amplifier  
Service in Black-and-White TV Receivers

#### Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC) . . . . .	6.3 ± 0.6	volts
Current at heater volts = 6.3 . . . . .	1.200	amp
Peak heater-cathode voltage:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 <sup>a</sup> max.	volts


Direct Interelectrode Capacitances (Approx):<sup>b</sup>

Grid No.1 to Plate . . . . .	0.26	pf
Input: G1 to (K+G3,G2,H). . . . .	15.0	pf
Output: P to (K+G3,G2,H). . . . .	6.5	pf

#### Mechanical:

Operating Position . . . . .	Any
Type of Cathode. . . . .	Coated Unipotential
Maximum Overall Length . . . . .	2.880"
Seated Length. . . . .	2.250" to 2.500"
Diameter . . . . .	1.438" to 1.562"
Dimensional Outline. . . . .	See <i>General Section</i>
Bulb . . . . .	T12
Base . . . . .	Large-Button Novar 9-Pin with Exhaust Tip (JEDEC No. E9-88)
Basing Designation for BOTTOM VIEW . . . . .	9NZ

- Pin 1 - Grid No.2
- Pin 2 - Grid No.1
- Pin 3 - Cathode,  
    Grid No.3
- Pin 4 - Heater



- Pin 5 - Heater
- Pin 6 - Grid No.1
- Pin 7 - Grid No.2
- Pin 8 - Do Not Use
- Pin 9 - Plate

#### Characteristics, Class A<sub>1</sub> Amplifier:

	Triode Connection <sup>c</sup>	Pentode Connection	
Plate Voltage. . . . .	150	60	250 volts
Grid-No.2 Voltage. . . . .	150	150	150 volts
Grid-No.1 Voltage. . . . .	-22.5	0	-22.5 volts
Amplification Factor . . . . .	4.4	-	-
Plate Resistance (Approx.) . . . . .	-	-	15000 ohms
Transconductance . . . . .	-	-	7100 μmhos
Plate Current. . . . .	-	390 <sup>d</sup>	70 ma
Grid-No.2 Current. . . . .	-	32 <sup>d</sup>	2.1 ma
Grid-No.1 Voltage (Approx.) for plate ma = 0.1 . . . . .	-	-	-42 volts



# 6GT5A

## HORIZONTAL-DEFLECTION AMPLIFIER

### Maximum Ratings, Design-Maximum Values:

*For operation in a 525-line, 30-frame system<sup>e</sup>*

DC Plate-Supply Voltage. . . . .	770 max.	volts
Peak Positive-Pulse Plate Voltage <sup>f</sup> . . . . .	6500 max.	volts
Peak Negative-Pulse Plate Voltage. . . . .	1500 max.	volts
DC Grid-No.2 (Screen-Grid) Voltage. . . . .	220 max.	volts
DC Grid-No.1 (Control-Grid) Voltage. . . . .	-55 max.	volts
Peak Negative-Pulse Grid-No.1 Voltage. . . . .	330 max.	volts
Cathode Current:		
Peak . . . . .	550 max.	ma
Average. . . . .	175 max.	ma
Grid-No.2 Input. . . . .	3.5 max.	watts
Plate Dissipation <sup>g</sup> . . . . .	17.5 max.	watts
Bulb Temperature (At hottest point on bulb surface) . . . . .	240 max.	°C

### Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

  For grid-resistor-bias operation . . . . . 1 max. megohm

<sup>a</sup> The dc component must not exceed 100 volts.

<sup>b</sup> without external shield.

<sup>c</sup> with grid No.2 connected to plate.

<sup>d</sup> This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.

<sup>e</sup> As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.

<sup>f</sup> This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

<sup>g</sup> An adequate bias resistor or other means is required to protect the tube in the absence of excitation.



## AVERAGE CHARACTERISTICS

