

# 8FQ7

## Medium-Mu Twin Triode

The 8FQ7 is the same as the 6FQ7 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	8.4	V
Warm-up time (Average) . . . . .	11	s

# 8GJ7

## Medium-Mu Triode—Sharp-Cutoff Pentode

The 8GJ7 is the same as the 6GJ7 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.300 ± 0.020	A
Voltage (AC or DC) at 0.300A . . . . .	8.0	V
Warm-up time (Average) . . . . .	11	s

# 8GN8

## High-Mu Triode—Sharp-Cutoff Pentode

The 8GN8 is the same as the 6GN8 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A . . . . .	8.0	V
Warm-up time (Average) . . . . .	11	s

# 8GU7

## Medium-Mu Twin Triode

The 8GU7 is the same as the 6GU7 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A. . . . .	8.4	V
Warm-up time (Average) . . . . .	11	s

