

# 8JU8A

## Quadruple Diode

The 8JU8A is the same as the 6JU8A except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A. . . . .	8.4	V
Warm-up time (Average) . . . . .	11	s

# 8JV8

## High-Mu Triode—Sharp-Cutoff Pentode

The 8JV8 is the same as the 6JV8 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	8.5	V
Warm-up time (Average) . . . . .	11	s

# 8KA8

## High-Mu Triode—Sharp-Cutoff Pentode

Pentode Unit Has Two Independent Control Grids

The 8KA8 is the same as the 6KA8 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	8.4	V
Warm-up time (Average) . . . . .	11	s

# 8LC8

## High-Mu Triode—Sharp-Cutoff Pentode

The 8LC8 is the same as the 6LC8 except for the following items:

### Heater Characteristics and Ratings

Current. . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	8.4	V
Warm-up time (Average) . . . . .	11	s

