

12J7-GT  
TO  
12Q7-GT



### 12J7-GT

#### SHARP-CUTOFF PENTODE

Heater, for Unipotential Cathode:  
Voltage . . . . . 12.6 . . . . . ac or dc volts  
Current . . . . . 0.15 . . . . . amp  
*The 12J7-GT is the same as the 6J7-GT except for heater rating.*

### 12K7-GT

#### REMOTE-CUTOFF PENTODE

Heater, for Unipotential Cathode:  
Voltage . . . . . 12.6 . . . . . ac or dc volts  
Current . . . . . 0.15 . . . . . amp  
*The 12K7-GT is the same as the 6K7-GT except for heater rating.*

### 12K8

#### TRIODE-HEXODE CONVERTER

Heater, for Unipotential Cathode:  
Voltage . . . . . 12.6 . . . . . ac or dc volts  
Current . . . . . 0.15 . . . . . amp  
*The 12K8 is the same as the 6K8 except for heater rating.*

### 12Q7-GT

#### TWIN DIODE—HIGH-MU TRIODE

Heater, for Unipotential Cathode:  
Voltage . . . . . 12.6 . . . . . ac or dc volts  
Current . . . . . 0.15 . . . . . amp  
*The 12Q7-GT is the same as the 6Q7-GT except for heater rating.*