



25Z6, 25Z6-GT/G

25Z6
25Z6-GT/G

HIGH-VACUUM RECTIFIER-DOUBLER

		Coated Unipotential Cathodes	
		25Z6	25Z6-GT/G
Heater Voltage	25		a-c or d-c volts
Current	0.3		amp.
Maximum Overall Length	3-1/4"		3-5/16"
Maximum Seated Height	2-11/16"		2-3/4"
Maximum Diameter	1-5/16"		1-5/16"
Bulb	Metal Shell, MT-8		T-9
Base	{ Small Wafer Octal 7-Pin 70		{ Intermed. Sh. Octal 7-Pin G-70
Basing Designation	{ 25Z6, Shell 25Z6-GT/G, No Con.		Pin 4 - Cathode #2 Pin 5 - Plate #1 Pin 7 - Heater Pin 8 - Cathode #1
Pin 1			Any
Pin 2			
Pin 3			
Mounting Position			

BOTTOM VIEW

Maximum Ratings Are Design-Center Values

RECTIFIER OR DOUBLER

Peak Inverse Plate Voltage	700 max. volts
Peak Plate Current per Plate	450 max. ma.
D-C Output Current per Plate	75 max. ma.
D-C Heater-Cathode Potential	350 max. volts

*Typical Operation as Half-Wave Rectifier with Condenser-Input Filter:**

Unless otherwise indicated, values are for both plates in parallel.

A-C Plate Supply Voltage per Plate (RMS)	117	150	235	volts
Filter Input Condenser	16	16	16	μf
Min. Total Effect. Plate-Supply Imped. per Plate	15	40	100	ohms
D-C Output Current per Plate	75	75	75	ma.
D-C Voltage (At input to filter):*				
At half-load current (75 ma.)	115	-	255	volts
At full-load current (150 ma.)	80	-	200	volts
Difference (Voltage Regulation)	35	-	55	volts
Percentage Regulation	30	-	22	%

Typical Operation as Voltage Doubler:

	Half-Wave	Full-Wave	
A-C-Plate Supply Voltage per Plate (RMS)	117	117	volts
Filter Input Condenser (Each)	16	16	μf
Min. Total Effect. Plate-Supply Imped. per Plate	30	15	ohms
D-C Output Current	75	75	ma.
D-C Voltage (At input to filter):*			
At half-load current (37.5 ma.)	-	250	volts
At full-load current (75 ma.)	-	205	volts
Difference (Voltage Regulation)	-	45	volts
Percentage Regulation	-	18	%

* In half-wave rectifier service, the two units may be used separately or in parallel.
* Approximate values.

Circuits and Plate Characteristic Curve for the 25Z6 and 25Z6-GT/G are the same as for Type 25Z5.

Mar. 20, 1943

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


DATA

2526



2526

OPERATION CHARACTERISTICS



NOV. 27, 1939

RCA VICTOR DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92C-4603 R2