

4AU6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4AU6 is the same as the 6AU6 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average)	11	sec

4AV6

Twin Diode—High-Mu Triode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4AV6 is the same as the 6AV6 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average)	11	sec

4BC5

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BC5 is the same as the 6BC5 except for the following items:

Heater Characteristics and Ratings (Design-Center Values):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average)	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode	200 max.	volts
Heater positive with respect to cathode	200 ^a max.	volts

^a The dc component must not exceed 100 volts.

