

*Substitute* **5Y4GT**  
10/64


## Full-Wave Vacuum Rectifier

The 5Y4GT is the same as the 5Y4GA except for the following items:

**Mechanical:**

- Operating Position. . . . . Vertical, base down or up, or  
Horizontal with pins 2 and 3 in vertical plane
- Maximum Overall Length. . . . . 3-3/8"
- Maximum Seated Length. . . . . 2-13/16"
- Maximum Diameter. . . . . 1-9/32"
- Dimensional Outline . . . . . See *General Section*
- Bulb. . . . . T9
- Base. . . . . Intermediate-Shell Octal 6-Pin,  
Arrangement 1 (JEDEC Group 1, No. B6-8), or  
Short Intermediate-Shell Octal 6-Pin  
with External Barriers, Arrangement 1  
(JEDEC Group 1, No. B6-60)
- Basing Designation for BOTTOM VIEW. . . . . 5Q

Pin 1 - No Connection  
Pin 2 - No Connection



Pin 3 - Plate No. 2  
Pin 5 - Plate No. 1  
Pin 7 - Filament  
Pin 8 - Filament

## 5Z3


## Full-Wave Vacuum Rectifier

The 5Z3 is the same as the 5U4G except for the following items:

**Mechanical:**

- Operating Position. . . . . Vertical, base down or up, or  
Horizontal with pins 1 and 4 in horizontal plane
- Maximum Overall Length. . . . . 5-3/8"
- Base. . . . . Medium-Shell Small 4-Pin (JEDEC No. A4-9)
- Basing Designation for BOTTOM VIEW. . . . . 4C

Pin 1 - Filament  
Pin 2 - Plate No. 2



Pin 3 - Plate No. 1  
Pin 4 - Filament

