

# 6GX6

## Sharp-Cutoff Pentode With Two Independent Control Grids

7-PIN MINIATURE TYPE  
For FM Sound-Detector Service

### GENERAL DATA

#### Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	6.3	volts
Current . . . . .	0.45 ± 6%	amp
Warm-up time (Average) . . . . .	11	sec

Direct Interelectrode Capacitances

(Approx.):<sup>a</sup>

Grid No.1 to plate . . . . .	0.022	μf
Grid No.1 to cathode & internal shield, grid No.3, grid No.2, and heater . . . . .	8	μf
Grid No.3 to plate . . . . .	1.6	μf
Grid No.1 to grid No.3 . . . . .	0.11	μf
Grid No.3 to cathode & internal shield, plate, grid No.2, grid No.1, and heater . . . . .	7.5	μf

#### Characteristics, Class A<sub>1</sub> Amplifier:

Plate Supply Voltage . . . . .	150	volts
Grid-No.3 Supply Voltage . . . . .	0	volts
Grid-No.2 Supply Voltage . . . . .	100	volts
Grid-No.1 Supply Voltage . . . . .	0	volts
Cathode Resistor . . . . .	180	ohms
Plate Resistance (Approx.) . . . . .	0.14	megohm
Transconductance, Grid No.1 to Plate . .	3700	μhos
Transconductance, Grid No.3 to Plate . .	750	μhos
Plate Current . . . . .	3.7	ma
Grid-No.2 Current . . . . .	3	ma
Grid-No.1 Supply Voltage (Approx.) for plate $\mu a = 20$ . . . . .	-4.5	volts
Grid-No.3 Supply Voltage (Approx.) for plate $\mu a = 20$ . . . . .	-7	volts

#### Mechanical:


Operating Position . . . . .	Any
Maximum Overall Length . . . . .	2-1/8"
Maximum Seated Length . . . . .	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip) . .	1-1/2" ± 3/32"
Diameter . . . . .	0.650" to 0.750"
Dimensional Outline . . . . .	See <i>General Section</i>
Bulb . . . . .	T5-1/2
Base . . . . .	Small-Button Miniature 7-Pin (JEDEC No.E7-1)



# 6GX6

Basing Designation for BOTTOM VIEW. . . . . 7EN

Pin 1 - Grid No.1  
 Pin 2 - Cathode,  
           Internal  
           Shield  
 Pin 3 - Heater



Pin 4 - Heater  
 Pin 5 - Plate  
 Pin 6 - Grid No.2  
 Pin 7 - Grid No.3

## FM SOUND-DETECTOR SERVICE

### Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE . . . . .	300	max.	volts
GRID-No.3 (CONTROL-GRID) VOLTAGE:			
Negative value (DC and Peak AC) . . . . .	100	max.	volts
Positive value (DC and Peak AC) . . . . .	25	max.	volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE. . . . .	300	max.	volts
GRID-No.2 VOLTAGE . . . . .	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section		
GRID-No.1 (CONTROL-GRID) VOLTAGE:			
Negative-bias value . . . . .	50	max.	volts
Positive-bias value . . . . .	0	max.	volts
GRID-No.2 INPUT:			
For grid-No.2 voltages up to 150 volts. . . . .	1	max.	watt
For grid-No.2 voltages between 150 and 300 volts . . . . .	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section		
GRID-No.3 INPUT . . . . .	0.1	max.	watt
PLATE DISSIPATION . . . . .	1.7	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode. . . . .	200	max.	volts
Heater positive with respect to cathode. . . . .	200 <sup>b</sup>	max.	volts

### Maximum Circuit Values:

Grid-No.3-Circuit Resistance. . . . .	0.68	max.	megohm
Grid-No.1-Circuit Resistance:			
For fixed-bias operation. . . . .	0.22	max.	megohm
For cathode-bias operation. . . . .	0.47	max.	megohm


<sup>a</sup> Without external shield.

<sup>b</sup> The dc component must not exceed 100 volts.



# 6GX6

## AVERAGE CHARACTERISTICS



92CM-11002




RADIO CORPORATION OF AMERICA  
Electron Tube Division  
Harrison, N. J.

DATA 2  
5-61

# 6GX6

## AVERAGE CHARACTERISTICS



92CM-11005


RADIO CORPORATION OF AMERICA  
Electron Tube Division

Harrison, N. J.



# 6GX6

## AVERAGE CHARACTERISTICS



92CM-11007




RADIO CORPORATION OF AMERICA  
Electron Tube Division  
Harrison, N. J.

DATA 3  
5-61

# 6GX6

## AVERAGE CHARACTERISTICS



92CM-11003


RADIO CORPORATION OF AMERICA  
 Electron Tube Division

Harrison, N. J.



# 6GX6

## AVERAGE CHARACTERISTICS



92CM-11006




RADIO CORPORATION OF AMERICA  
Electron Tube Division  
Harrison, N. J.

DATA 4  
5-61

# 6GX6

## AVERAGE GRID-No.1 OPERATION CHARACTERISTIC



92CS-11004

